


## VK10-K100-19



### Contact

Jutta Geurtz  
+49 2336 808 364  
jgeurtz@titan-schwelm.de



### Would you like to have it one size bigger?

Many things characterise VK10 heads by TITAN. A powerful argument is the wide range of products offering the right solution for each intended use of polyester strap.

The VK10-K100-19 is the third of the series. The larger brother of the sub-type VK10-K50-13 and VK10-K85-16 further increases performance. In plain language this means: higher strap tension for larger packages such as slit coils, pipes and profiles.

The minimum contact surface is 100 mm. This head is suitable for a strap width from 16 to 19 mm at a maximum thickness of 1.23 mm.

The VK10-100-19 has proven its durability in practical use worldwide.

### Technical Data

Kind of drive	Electric
Tension force	max. 3,200 N (depending on strap)
Mains voltage	400 V AC / 50 Hz
Control voltage	24 V DC
Connected load	0.9 kW
Current consumption	4 A
Strap conveying speed	approx. 2.5 m/s (depending on strap thickness) approx. 4,5 m/s (depending on strap thickness) - optional approx. 8.2 ft/s (depending on strap thickness)

	approx. 14.8 ft/s (depending on strap thickness) - optional
Dimensions	453 x 640 x 450 mm (L x W x H) 17.8 x 25.2 x 17.7" (L x W x H)
Weight	80 kg 176.4 lb

### Strap/Joint

Type of strap	Plastic strap
Strap	PP PET
Strap width	16 mm 5/8" 16, 19 mm 5/8" ; 3/4"
Strap thickness	0.75 - 1.35 mm 0.030 - 0.053" 0.7 - 1.35 mm 0.028 - 0.053"
Kind of seal	Thermo-weld joint
Sealing strength (depending on strap quality, strap dimensions)	up to 60% of the strap breaking load (depending on the use of the heating control)

### Minimum bearing area

Expansive package	90 mm 3.5"
Slit coil ring	100 mm 3.9"
Hexagon pipe bundle	110 mm 4.3"
Round package	Ø 500 mm Ø 19.7"

### Application

Coil strapping of small packages like coils, slit coils, pipes, wire, etc. with high strap tension and material strength