

SPZ



#### Contact

Jutta Geurtz  
+49 2336 808 364  
jgeurtz@titan-schwelm.de



## Pneumatic sealer for steel strap

### "Simple" in two variants

If you need a simple steel strap sealer for circular and flat packages, the SPZ from TITAN is the best choice. To sum up its characteristics: Robust pneumatic technology, ergonomic design, a weight of just 3.3 kg and single-notch seal joint for seal types RSK / RSL 19, RSK / RSL 25 and RSK / RSL 32. Handling and operation are intuitive, and maintenance is very user-friendly. By the way: This simple tool is available in two variants:

Thanks to their different grip angles, SPZ-E and SPZ-W meet the needs of a wide range of users. The matching tensioner for the SPZ is the TITAN PR33; if one notch is not enough, you can resort to the TITAN DPZ-L with double notch.

### Technical Data

Kind of drive (sealing)	Pneumatic
Seal (Type)	RSK, RSL
Dimensions	300 x 210 x 240 mm (L x W x H) 11.8 x 8.3 x 9.4" (L x W x H)
Weight	3.3 kg 7.3 lb
Air pressure	max. 6 bar flow pressure

### Strap/Joint

Type of strap	Steel strap
---------------	-------------

Strap	Automatenband MEGABAND®
Strap width	19, 25, 32 mm 3/4" ; 1" ; 1 1/4"
Strap thickness	0.80 - 1.00 mm (for Automatenband) 0.80 mm (for MEGABAND®) 0.031 - 0.039" (for Automatenband) 0.031" (for MEGABAND®)
Kind of seal	Seal-joint (single notch)

### **Application**

Strapping of packages and palletized goods with small contact surfaces.